

Broadband high energy diode pumped Yb:KYW multipass amplifier

Dimitris N. Papadopoulos, Alain Pellegrina, Patricia Ramirez, Patrick Georges, Frédéric Druon

▶ **To cite this version:**

Dimitris N. Papadopoulos, Alain Pellegrina, Patricia Ramirez, Patrick Georges, Frédéric Druon. Broadband high energy diode pumped Yb:KYW multipass amplifier. Optics Letters, 2011, 36 (19), pp.3816-3818. hal-00621039

HAL Id: hal-00621039
https://hal.science/hal-00621039

Submitted on 9 Sep 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Broadband high energy diode pumped Yb:KYW multipass amplifier

Dimitrios N. Papadopoulos,[1*] Alain Pellegrina,[1] Lourdes Patricia Ramirez,[2] Patrick Georges,[2] and Frédéric Druon[2]

[1]*Institut de la Lumière Extrême, CNRS, Ecole Polytechnique, ENSTA Paristech, Institut d'Optique, Palaiseau cedex, France*
[2]*Laboratoire Charles Fabry, UMR 8501, Institut d'Optique, CNRS, Univ Paris Sud 11, 2, Avenue Augustin Fresnel, 91127 Palaiseau cedex, France*
**Corresponding author: dimitris.papadopoulos@institutoptique.fr*

Received Month X, XXXX; revised Month X, XXXX; accepted Month X, XXXX; posted Month X, XXXX (Doc. ID XXXXX); published Month X, XXXX

We report a diode pumped Yb:KYW amplifier delivering up to 27 mJ pulses at a repetition rate of 100 Hz and a spectral bandwidth of 5.5 nm, centered at around 1030 nm. The system is based on a double-head multipass amplifier configuration where the pump thermal load is distributed over two relatively thin laser crystals which permits a sufficiently large number of passes with minimal passive losses thus maximizing the energy extraction efficiency. The amplified pulse bandwidth theoretically supports 340 fs pulses and as a demonstration, a small fraction of the amplified pulses has been compressed to 560 fs. © 2011 Optical Society of America

OCIS Codes: 140.3280, 140.3615, 140.7090

Ultrafast diode pumped laser systems are of great interest either as direct high intensity systems or as pump sources for OPCPA based systems operating in the extremely short pulse duration regime. Yb-doped materials, due to the excellent Yb^{3+} ion's spectroscopic properties as well as their thermal management advantages have been extensively investigated in this general context [1]. The most widely studied material is Yb:YAG as it combines both high gain and high thermal conductivity that has recently resulted in the amplification of picoseconds pulses to the Joule level [2-4]. The main limitation however of this material is the available amplification bandwidth, which in the case of high energy systems, restricts its application in the ps regime. Yb:CaF_2 on the other hand is a very promising material mainly because of its broad gain bandwidth and high energy storage capacity. Regenerative amplification to several mJ in the kHz regime, both at room temperature and for cryogenically cooled crystals [5,6], as well as Joule level amplification in the femtosecond regime at 10 Hz [7] have been recently demonstrated. The main limitation in this case is the very high saturation fluence of Yb:CaF_2, resulting in low gain amplifiers or reduced energy extraction efficiencies. Ideally Yb:CaF_2 could be used in the final energetic stages of an amplification chain seeded by a sufficiently high energy, broadband signal to fully exploit its advantages. On the other hand, Yb-doped tungstates (Yb:KGW, Yb:KYW, Yb:KLuW) are well known both for their high gain and broad bandwidth and seem to be the right alternative towards a medium energy level amplification of broad bandwidth pulses. But due to their relatively limited energy storage capacity (with an upper state lifetime of 300 μs) they have been so far restricted to relatively low energy applications at high repetition rates.

In the framework of the Institut de la Lumière Extrême (ILE) project and the 10 PW Apollon source front end development, we study the development of a 100 Hz broadband Yb:KYW multi-mJ level ($\Delta\lambda$>3.5 nm, E>20 mJ), multipass preamplifier for Yb:CaF_2 based main amplifiers to reach the required final Joule level output.

Several works have been reported on Yb:KYW or Yb:KGW in both regenerative and multipass configurations. The highest energy achieved so far from a diode pumped system based on a cryogenically cooled Yb:KYW regenerative amplifier, has been limited to 5.5 mJ [8], while pulses as short as 190 fs have been reported for sub-mJ setups [9]. 25 mJ pulses have been also reported but based on a low efficiency and complex Ti:Sapphire pumped Yb:KGW regenerative amplifier operating at 1 Hz [10].




Fig. 1. Experimental setup. Schematic of the CPA injection system (bottom part). Double head Yb:KYW multipass amplifier (upper part).

In this study, we present a multipass amplifier based on a diode pumped Yb:KYW crystal operating at room temperature and delivering pulses with energies up to 27 mJ at 100 Hz (2.7 W average power). This is the highest energy ever reported for a Yb:KYW based amplifier. The overall optical-to-optical efficiency of the system is around 15% with an extraction efficiency estimated to be greater than 70%. The achieved bandwidth at the maximum energy is 5.5 nm, corresponding to 340 fs Fourier transform limited (FTL) pulses which, when compared to

previously reported results, is an improvement by a factor of at least 2 for this type of amplifier and energy level.

In Figure 1, the general schematic of the complete chirped pulse amplification (CPA) chain studied here is presented. The starting point is a very broadband Ti:Sapphire (Rainbow from Femtolasers) oscillator delivering sub-7 fs pulses at 800 nm with a spectral content that is well extended in the 1030 nm regime. About 4 pJ pulses around 1030 nm are filtered and separated at the output of the oscillator. These pulses are first amplified in a Yd-doped fiber amplifier (Keopsys) to 4 nJ and then stretched in a classical double pass grating stretcher (stretching factor: 0.5 ns/nm). The following amplifier consists of a diode-pumped Yb:KYW regenerative amplifier (Amplitude Systemes) delivering pulses up to 2 mJ. The repetition rate of this amplifier is adjustable up to 1 kHz while the output spectrum can be finely tuned by an intracavity polarizer. In these experiments, the repetition rate was fixed at 100 Hz and the output spectrum was centered at 1030 nm with a bandwidth of 4.5 nm.

In the upper part of Fig.1, we present a detailed design of the amplifier under study. The amplifier is very compact, covering an area of only 1.15x0.3 m^2. The whole CPA setup could fit in less than half of an optical table. It is composed of a simple folded 4f imaging cavity where two laser crystals are used as end mirrors. The laser crystals are two identical 0.5° wedged, 5x5mm Yb:KYW disks of 700 µm thickness at b-cut (E//a) and 5% doping level. The crystals are soldered on a metal mount that is cooled by circulating water at about 18 °C.

The specific cavity design permits both a large number of passes with minimal losses, but most importantly, the combination of two relatively thin amplifying disks that results in the pump thermal load distribution. As shown in Fig. 1, the crystals are pumped in series by a unique fiber coupled diode with a 400 µm core diameter, delivering up to 400 W at 981 nm (LIMO). The diode operates in QCW regime with variable repetition rate and pulse duration, allowing the fine temperature adjustment of the emission wavelength exactly to 981 nm (to match the absorption peak of Yb:KYW), with ~3.7 nm bandwidth. The repetition rate in these experiments is set at 100 Hz and the pulse duration at 450 µs, corresponding to 180 mJ pulse energy (18 W). At maximum pump power, about 135 mJ (75%) are absorbed in both crystals (~86 mJ in the first crystal and 49 mJ in the second one).

Only about 37 mJ is estimated to be the actual total stored energy. This is not surprising since for the relatively high incident pump intensity of more than 22 kW/cm^2 (5 times the saturation intensity of the Yb:KYW for unpolarized pump), the effective storage time is reduced to $\tau_{sto} \approx 50$ µsec ($\tau_{sto} = \tau_{fluo}/(1+I_p/I_{sat})$). The 450 µsec long pump pulses were chosen however in order to increase the stored energy (with an upper duration limit set by the crystals thermal load) but at the cost of decreasing the global energy storage efficiency.

In the optimal cavity configuration, the beam passes 11 and 10 times through the first and the second crystal respectively (a complete round trip inside the crystal is counted as one pass). Both pump and signal diameter on the crystals planes is 1.5 mm. The cavity is optimized by adjustment of the folding mirror (M_f) position to compensate the induced lensing by the laser disks estimated (at maximum pump power) around 10-12 m. The cavity passive losses have been estimated at ~15% by replacing the two crystals with high reflection mirrors. The amplifier operates in air environment and no vacuum is required.




Fig. 2. a) Output energy as a function of the input energy for maximum pump energy (180 mJ). The dashed line curve corresponds to the simulated output ($E_{sto,tot}$: the total stored energy, $J_{sto,1/2}$: the stored fluence for each crystal, $g_{0,1/2}$: the small signal gain coefficient for each crystal). b) Output energy as a function of the incident pump energy for different input pulse energy at 100 Hz.

In Figure 2a, we plot the the output energy as a function of the signal energy at maximum pump power. We also plot the predicted (dashed line) output energy based on a Frantz-Nodvik model, taking into account the measured pump absorption and passive losses as well as the calculated total stored energy and its relative distribution in each crystal (model parameters are indicated in the figure). For a 2 mJ input, we obtained 27 mJ at the output, well into the saturated, energy extraction regime of operation of our amplifier. In Figure 2b, we plot the output energy as a function of the total incident pump energy for various input pulse energy levels (0.2-2 mJ) at 100 Hz. For 140 mJ pump power, we observe the reduction of the efficiency slope due to the pump absorption saturation and energy storage efficiency reduction. It is also interesting to notice that the output energy barrier of 20 mJ is still surpassed for ~0.5 mJ input (40x gain). At maximum output energy the global efficiency is 15% and the extraction efficiency ~72%.

In Figure 3, the input and output beam profiles of the amplifier are given for increasing pump energy. The M^2 of the beam was optimized for maximum pump power and

measured to be better than 1.2 in both directions (1.1 for the input beam), indicating a high quality output beam. The main difficulty at this point was the rising astigmatism induced by the laser crystal with increasing pump power [11]. For moderate pump power level (<20W), proper orientation of the crystals (common for both crystals) and respecting the E//a polarization direction, could be beneficially used to compensate the small input beam astigmatism (comparison of beam profiles at E_p=90 and 180 mJ in Fig. 3). Further increase of the repetition rate was possible up to 200 Hz but with a moderate output energy reduction of 10-15% due to the progressive thermal degradation of the beam quality and increasing crystal temperature. Above 200 Hz however the induced asymmetric thermal lens resulted in strong beam diffraction at the edges of the cavity mirrors and the fast decrease of the output energy.




Fig. 3. Input and output beam profiles (near field) for 90 mJ, 120 mJ and 180 mJ pump energy at 100Hz (E_{in}=1mJ).




Fig. 4. Output spectrum as a function of the output energy for E_{in}=1mJ (dashed line curve corresponds to the input spectrum). Inset : autocorrelation trace of the recompressed pulses at 22 mJ.

The stability of the system has been also examined. At 27 mJ output and over 20 minutes, the pulse-to-pulse rms variation was measured to be 0.8% (0.4% at the input). The beam pointing stability was found <50 µrad.

The evolution of the output spectrum as a function of the output energy is also examined. In Figure 4, we plot the input/output spectra for 1 mJ input energy and for 8 to 22 mJ output energy. We observe the spectrum progressive blue shift towards 1025 nm, resulting in a rectangular-like spectrum of 5.5 nm bandwidth at 22 mJ. This behavior is the combined result of (i) the Yb:KYW (E//a) gain peak around 1025 nm, (ii) the gain saturation in combination to the CPA that counteracts the blue shift and (iii) the specific spectral form of the input pulses centered at 1030 nm, extending to almost 1025 nm. This spectral bandwidth corresponds to about 340 fs FTL pulses. As a demonstration of the compressibility of these pulses, based on a matched grating compressor, a small fraction of the output (few µJ) has been compressed around 560 fs (Fig. 4 inset), about 1.6 times the FTL duration This deviation is most probably due to the complicated higher order spectral phase generated in the Ti:Sapphire oscillator in the 1030 nm regime.

In conclusion, we presented the development of an Yb:KYW multipass amplifier that delivers broadband pulses of 5.5 nm on a record energy level of 27 mJ. The system operates at a high repetition rate of 100 Hz, providing 2.7 Watts of average power with an excellent beam quality. Scaling of the amplifier performance in terms of output energy seems to be possible based on the use of slightly thicker crystals. According to our model, replacing both crystals with 1 mm thick crystals would result in more than 50 mJ output energy. The repetition rate in this case, could be maintained at 100 Hz with a carefully designed cavity and proper cut of the crystal to compensate the astigmatic thermal lens [11].

This work has been funded by the ILE 07-CPER 017-01 contract.

References

1. S. Klingebiel, C. Wandt, C. Skrobol, I. Ahmad, S. A. Trushin, Z. Major, F. Krausz, S. Karsch, Opt. Express **19**, 5357-5363 (2011).
2. F. J. Furch, B. A. Reagan, B. M. Luther, A. H. Curtis, S. P. Meehan, and J. J. Rocca, Opt. Lett. **34**, 3352-3354 (2009).
3. J. Tümmler, R. Jung, H. Stiel, P. V. Nickles, and W. Sandner, Opt. Lett. **34**, 1378-1380 (2009).
4. A. H. Curtis, B. A. Reagan, K. A. Wernsing, F. J. Furch, B. M. Luther, and J. J. Rocca, Opt. Lett. **36**, 2164-2166 (2011).
5. S. Ricaud, F. Druon, D. N. Papadopoulos, P. Camy, J. L Doualan, R. Moncorgé, M. Delaigue, Y. Zaouter, A. Courjaud, P. Georges, and E. Mottay, Opt. Lett. **35**, 2415-2417 (2010).
6. A. Pugžlys, G. Andriukaitis, A. Baltuška, L. Su, J. Xu, H. Li, R. Li, W. J. Lai, P. B. Phua, A. Marcinkevičius, M. E. Fermann, L. Giniūnas, R. Danielius, and S. Ališauskas, Opt. Lett. **34**, 2075-2077 (2009).
7. M. Siebold, M. Hornung, R. Boedefeld, S. Podleska, S. Klingebiel, C. Wandt, F. Krausz, S. Karsch, R. Uecker, A. Jochmann, J. Hein, and M. C. Kaluza, Opt. Lett. **33**, 2770-2772 (2008).
8. K. Ogawa, Y. Akahane, M. Aoyama, K. Tsuji, S. Tokita, J. Kawanaka, H. Nishioka, and K. Yamakawa, Opt. Express **15**, 8598-8602 (2007).
9. A. Buettner, U. Buenting, D. Wandt, J. Neumann, and D. Kracht, Opt. Express **18**, 21973-21980 (2010).
10. H. Liu, J. Nees, G. Mourou, S. Biswal, G. J. Spühler, U. Keller and N. V. Kules, Opt. Commun. **203**, 315-321 (2002).
11. V. V. Filippov, N. V. Kuleshov, I. T. Bodnar, Appl. Phys. B **87**, 611-614, (2007).

References (with titles)

1. Sandro Klingebiel, Christoph Wandt, Christoph Skrobol, Izhar Ahmad, Sergei A. Trushin, Zsuzsanna Major, Ferenc Krausz, and Stefan Karsch, "High energy picosecond Yb:YAG CPA system at 10 Hz repetition rate for pumping optical parametric amplifiers," Opt. Express **19**, 5357-5363 (2011)
2. Federico J. Furch, Brendan A. Reagan, Bradley M. Luther, Alden H. Curtis, Shaun P. Meehan, and Jorge J. Rocca, "Demonstration of an all-diode-pumped soft x-ray laser," Opt. Lett. 34, 3352-3354 (2009)
3. J. Tümmler, R. Jung, H. Stiel, P. V. Nickles, and W. Sandner, "High-repetition-rate chirped-pulse-amplification thin-disk laser system with joule-level pulse energy," Opt. Lett. **34**, 1378-1380 (2009)
4. A. H. Curtis, B. A. Reagan, K. A. Wernsing, F. J. Furch, B. M. Luther, and J. J. Rocca, "Demonstration of a compact 100 Hz, 0.1 J, diode-pumped picosecond laser," Opt. Lett. **36**, 2164-2166 (2011)
5. Sandrine Ricaud, Frédéric Druon, Dimitris N. Papadopoulos, Patrice Camy, Jean-Louis Doualan, Richard Moncorgé, Martin Delaigue, Yoann Zaouter, Antoine Courjaud, Patrick Georges, and Eric Mottay, "Short-pulse and high-repetition-rate diode-pumped Yb:CaF2 regenerative amplifier," Opt. Lett. 35, 2415-2417 (2010)
6. A. Pugžlys, G. Andriukaitis, A. Baltuška, L. Su, J. Xu, H. Li, R. Li, W. J. Lai, P. B. Phua, A. Marcinkevičius, M. E. Fermann, L. Giniūnas, R. Danielius, and S. Ališauskas, "Multi-mJ, 200-fs, cw-pumped, cryogenically cooled, Yb,Na:CaF2 amplifier," Opt. Lett. 34, 2075-2077 (2009)
7. Mathias Siebold, Marco Hornung, Ragnar Boedefeld, Sebastian Podleska, Sandro Klingebiel, Christoph Wandt, Ferenc Krausz, Stefan Karsch, Reinhard Uecker, Axel Jochmann, Joachim Hein, and Malte Christoph Kaluza, "Terawatt diode-pumped Yb:CaF2 laser," Opt. Lett. 33, 2770-2772 (2008)
8. K. Ogawa, Y. Akahane, M. Aoyama, K. Tsuji, S. Tokita, J. Kawanaka, H. Nishioka, and K. Yamakawa, "Multi-millijoule, diode-pumped, cryogenically-cooled Yb:KY(WO4)2 chirped-pulse regenerative amplifier," Opt. Express 15, 8598-8602 (2007)
9. A. Buettner, U. Buenting, D. Wandt, J. Neumann, and D. Kracht, "Ultrafast double-slab regenerative amplifier with combined gain spectra and intracavity dispersion compensation," Opt. Express 18, 21973-21980 (2010)
10. H. Liu, J. Nees, G. Mourou, S. Biswal, G. J. Spühler, U. Keller and N. V. Kules, "Yb:KG(WO4)2 chirped-pulse regenerative amplifiers," Opt. Commun. 203, 315-321 (2002)
11. V. V. Filippov, N. V. Kuleshov, I. T. Bodnar, "Negative thermo-optical coefficients and athermal directions in monoclinic KGd(WO4)2 and KY(WO4)2 laser host crystals in the visible region, " Appl. Phys. B **87**, 611-614, (2007)